

400 Seventh Street, S.W. Washington, D.C. 20590

Pipeline and Hazardous Materials Safety Administration

DOT-SP 6530 (THIRTEENTH REVISION)

(FOR RENEWAL, SEE 49 CFR § 107.109)

- 1. GRANTEE: (See individual authorization letter)
- 2. PURPOSE AND LIMITATION:
 - a. This special permit authorizes the transportation in commerce of hydrogen and mixtures of hydrogen with helium, argon or nitrogen, in certain cylinders filled to 110 percent of their marked service pressures. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
 - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
 - c. Unless otherwise stated herein, this special permit consists of the special permit authorization letter issued to the grantee together with this document.
- 3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
- 4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.302a(b) in that flammable gases are not authorized for special filling limits in DOT specification cylinders except as specified herein.

- 5. <u>BASIS</u>: This special permit is based on the application of Air Products and Chemicals, Inc. dated June 21, 2004, submitted in accordance with § 107.109.
- 6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Proper Shipping Name/ Hazardous Materials Description	Hazard Class/ Division	Identi- fication Number	Packing Group
Compressed gas, n.o.s. (mixtures containing hydrogen)	2.2	UN1956	N/A
Compressed gas, flammable, n.o.s.	2.1	UN1954	N/A
Hydrogen, compressed	2.1	UN1049	N/A

- 7. SAFETY CONTROL MEASURES: Prescribed packagings are DOT Specification 3A, 3AA, 3AX or 3AAX steel cylinders, not over 35 years old, that are filled to 110% of their marked service pressure, must conform to the conditions prescribed in § 173.302a(b) and the following:
 - a. DOT Specification 3A and 3AX cylinders are limited to those having an intermediate manganese composition.
 - b. Cylinders manufactured from intermediate manganese steel must have been normalized, not quenched and tempered. Quench and temper treatment of intermediate manganese steel is not authorized.
 - c. Cylinders from chrome moly steel must have been quenched and tempered, not normalized. Use of normalized chrome moly cylinders is not permitted.

8. SPECIAL PROVISIONS:

a. A person who is not a holder of this special permit who receives a package covered by this special permit may reoffer it for transportation provided no modification or change is made to the package or its contents and it is reoffered for transportation in conformance with this special permit and the HMR.

- b. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.
- c. Cylinders must be equipped with safety relief devices as follows:
 - (1) Cylinders less than 65 inches in length must be equipped with fusible metal backed frangible disc devices.
 - (2) Cylinders 65 inches or greater in length and 9-5/8 inches in diameter or larger must be equipped with fusible metal backed frangible disc devices or frangible disc devices except cylinders having diameter of 22 inches or larger must be equipped with frangible disc devices.
- d. Each cylinder or manifolded group of cylinders must be conspicuously marked "DOT-SP 6530." Tube-trailers must have this marking displayed on the right side, near the front, in letters not less than 2 inches high on a contrasting background. Cylinders marked "DOT-SP 6530" prior to December 30, 1976, may be transported under the terms of this special permit.
- e. Packagings permanently marked 'DOT-E 6530', prior to October 1, 2007 may continue to be used under this special permit for the remaining service life of the packaging or until the special permit is no longer valid. Packagings marked on or after October 1, 2007 must be marked 'DOT-SP 6530'.
- f. Shipping papers displaying 'DOT-E 6530' may continue to be used until October 1, 2007, provided the special permit remains valid.
- 9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle and rail freight.
- 10. MODAL REQUIREMENTS: None as a requirement of this special permit.

- 11. <u>COMPLIANCE</u>: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 <u>et seq</u>:
 - o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
 - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when the special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU) - 'The Hazardous Materials Safety and Security Reauthorization Act of 2005' (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term 'exemption' to 'special permit' and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 - Immediate notice of certain hazardous materials incidents, and 171.16 - Detailed hazardous

materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:

for Robert A. McGuire
Associate Administrator

for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, Department of Transportation, Washington, D.C. 20590. Attention: PHH-31.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm
Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: sln